



STC ARCHITECTURAL FILMS

METALIZED	VISUAL LIGHT TRANSMITTED (VLT)	TOTAL SOLAR ENERGY REJECTED (TSER)	UV REJECTED 380NM	THICKNESSS	PLY	OUTLOOK	OUT/IN
SILVER 05	5	83	99%	1.5mil	2	REFLECTIVE	SIL/SIL
SILVER 15	15	79	99%	1.5mil	2	REFLECTIVE	SIL/SIL
GREY BLUE	14	76	99%	1.5mil	2	REFLECTIVE	GB/SIL
BRONZE	14	76	99%	1.5mil	2	REFLECTIVE	BRZ/SIL
BURNISHED GOLD	8	81	99%	1.5mil	2	REFLECTIVE	GLD/SIL
FOREST GREEN	8	81	99%	1.5mil	2	REFLECTIVE	GRN/SIL
CERAMIC							
CRYSTAL 60GS	61	57	99%	2.0mil	2	LOW REFLECTIVE	
CRYSTAL 70	70	54	99%	1.5mil	1	NON REFLECTIVE	
UV 400 REJECTING			UV REJECTED 400nm				
SCF HPS 35	35	68	99.50%	3mil	Multi Layer	LOW REFLECTIVE	
SCF HPS 50	50	60	99.50%	3mil	Multi Layer	LOW REFLECTIVE	
SCF 70	69	54	99.50%	1.9mil	Multi Layer	NON REFLECTIVE	
SCF 80	78	35	99.50%	1.9mil	Multi Layer	NON REFLECTIVE	

Note:

This information is the best currently available on the subject. The result should, however, only be regarded as a general guide to material properties and not as a guarantee. Some of the properties can be changed as a result of the supplier's effort to improve the quality or production efficiency